

## Xtenna™ PoE Switch 4 / 8 Port · 16 Port · 24 Port



### XTENNA™ PoE Switch – Technical Specifications

	4 / 8 Port	16 Port	24 Port
Standards	IEEE 802.3af IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3x Flow Control		
Ports	8 10/100BaseT(X)	16 10/100BaseT(X)	24 10/100BaseT(X)
PSE/PoE Ports	4 or 8	16	24
Features	MAC Address: 1K Buffer Memory: 512K bits Transmission Method: Store and Forward		
Filtering/Forwarding Rates	100Mbps port: 148,800pps 10Mbps port: 14,880pps		
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP		
LED Indicators	Per Port: Link/Act, PoE Act/Status Per Unit: Power		
Power Input	90~260V/AC, 50~60Hz		
Power Output	48V/DC Per Port Output – 15.4W Max Per Port		
Full Output Supported	4 Ports / 8 Ports	16 Ports	24 Ports
Max Power Consumption	65W / 130W	260W	390W
Dimensions (L x W x H)	266 x 160 x 44mm	440 x 220 x 44mm	440 x 220 x 44mm
Weight	1.3kg / 1.6kg	3.8kg	5.5kg
Operating Temperature	0 to 55°C		
Storage Temperature	-20 to 90°C		
Humidity	10 to 90% RH (non-condensing)		
Certifications	FCC Class A, CE		

EsSEN reserves the right to modify specifications without notice.

© 2013 EsSEN



#### EsSEN Energy Conversion Devices Pvt Ltd

24 B, Jolly Maker II, Nariman Point, Mumbai 400 021 INDIA  
Tel: +91 22 6632 5363 • Fax: +91 22 6632 5366  
Email: xtenna@essenrfid.com • Web: www.essenrfid.com

#### Syscomp

1 Woodgrove Turn, Warren  
NJ 07059 USA  
Tel: 1-732-604-3055  
Email: harish\_purohit@essenrfid.com

#### Mr. James Snyder

2913 SW 22nd Cir #36D  
Delray Beach, FL 33445 USA  
Tel: 1-561-272-6227  
Email: james@essenrfid.com